

CIT311 List of Questions

Latex formatted questions may not properly render

Q1 Why is the destination address examined in the header while routing the packets in datagram switching?

- ☒ For determination of next hop in the path towards the destination
- ☐ For determination of previous hop in the path towards the destination
- ☐ For determination of next hop generated from the source
- ☐ For determination of previous hop generated from the source

Q2 message handling system model in ISDN is used for remote operations and reliable transfer server.

- ☐ X.400
- ☐ X.401
- ☐ X.408
- ☒ X.410

Q3 are used for negotiating the network facilities for supporting additional services such as direct inward dialing, call forwarding etc.

- ☐ Call establishment message
- ☐ Call control message
- ☐ Call disconnect message
- ☒ Other message

Q4 The first generation of ISDN is called as a narrowband ISDN which has a orientation.

- ☒ circuit switching
- ☐ datagram packet switching
- ☐ message switching
- ☐ virtual circuit packet switching

Q5 When does the fixed path get established between the source and destination in the virtual packet switching network?

- ☒ Before the transmission of packets
- ☐ After the transmission of packets
- ☐ During the transmission of packets
- ☐ All of the above

Q6 The sequence of the packetized information to be transmitted between the nodes in an establishment phase of virtual packet switching is _____

- ☐ unidirectional in nature
- ☒ bidirectional in nature
- ☐ multi-directional in nature
- ☐ unpredictable in nature

Q7 In transport layer, a message is normally divided into transmittable

- ☒ Segments
- ☐ Signals
- ☐ Networks
- ☐ Frames

Q8 Asynchronous Transfer Mode (ATM) technology was originally designed as a

- ☐ LAN Technology
- ☒ WAN Technology

- ☐ DSL Technology
- ☐ IP Technology

Q9 Which of the following is done in the physical layer of the ATM network?

- ☐ Cell multiplexing and demultiplexing
- ☐ Generic flow control
- ☐ Transmission frame generation/recovery
- ☐ Monitoring of the user information field for bit errors and possible corrective actions

Q10 Why is ATM the goal for future networking?

- ☐ It is efficient for data transfer.
- ☐ It's the only technology suitable for transmission of digital television.
- ☐ It allows the integration of voice, data and video into one network.
- ☐ It creates an error free network.

Q11 ATM is fundamentally a

- ☐ Circuit switching
- ☐ Packet switching
- ☐ Narrow band
- ☐ None of these

Q12 ATM technology supports different types of connections between two

- ☐ Stations
- ☐ Switches
- ☐ End Users
- ☐ Packages

Q13 X.25 standard specifies

- ☐ data bit rate
- ☐ technique for start-stop data
- ☐ technique for dial access
- ☐ DTE/DCE interface

Q14 The main important technical contribution of B-ISDN is the

- ☐ SMDS
- ☐ Frame relay
- ☐ X.25
- ☐ ATM

Q15 The main important technical contribution of narrowband ISDN is

- ☐ SMDS
- ☐ Frame relay
- ☐ X.25
- ☐ ATM

Q16 Why is the destination address examined in the header while routing the packets in datagram switching?

- ☐ For determination of next hop in the path towards the destination
- ☐ For determination of previous hop in the path towards the destination
- ☐ For determination of next hop generated from the source
- ☐ For determination of previous hop generated from the source

Q17 ----- connect nodes across an Internetwork regardless of the Physical Layer and Data Link Layer protocol that is used.

- ☐ Repeater
- ☐ Switch
- ☒ Router
- ☐ Hub

Q18 The maximum hop count for RIP is?

- ☐ 10
- ☒ 15
- ☐ 20
- ☐ 25

Q19 One of the following is not a Routing Protocol

- ☐ RIP
- ☐ EIGRP
- ☐ OSPF
- ☒ IEPR

Q20 OSPF is a

- ☐ Distance vector protocol
- ☒ Link state protocol
- ☐ Autonomous system protocol
- ☐ None of the options

Q21 Which protocol working at the Transport layer provides a connectionless service between hosts?

- ☐ IP
- ☐ ARP
- ☐ TCP
- ☒ UDP

Q22 CRC stands for

- ☒ cyclic redundancy check
- ☐ code repeat check
- ☐ code redundancy check
- ☐ cyclic repeat check

Q23 Header of a frame generally contains

- ☐ synchronization bytes
- ☐ addresses
- ☐ frame identifier
- ☒ all of the mentioned

Q24 Which one of the following task is not done by data link layer?

- ☐ framing
- ☐ error control
- ☐ flow control
- ☒ channel coding

Q25 The data link layer takes the packets from _____ and encapsulates them into frames for transmission.

- ☒ network layer
- ☐ physical layer
- ☐ transport layer
- ☐ application layer

Q26 A single channel is shared by multiple signals by

- ☐ analog modulation
- ☐ digital modulation
- ☒ multiplexing
- ☐ none of the mentioned

Q27 Wireless transmission can be done via

- ☐ radio waves
- ☐ microwaves
- ☐ infrared
- ☒ all of the mentioned

Q28 The physical layer translates logical communication requests from the _____ into hardware specific operations.

- ☒ data link layer
- ☐ network layer
- ☐ transport layer
- ☐ application layer

Q29 The physical layer is responsible for

- ☐ line coding
- ☐ channel coding
- ☐ modulation
- ☒ all of the mentioned

Q30 In the layer hierarchy as the data packet moves from the upper to the lower layers, headers are

- ☒ Added
- ☐ Removed
- ☐ Rearranged
- ☐ Modified

Q31 Which transmission media has the highest transmission speed in a network?

- ☐ coaxial cable
- ☐ twisted pair cable
- ☒ optical fiber
- ☐ electrical cable

Q32 The _____ is the physical path over which a message travels

- ☐ Path
- ☒ Medium
- ☐ Protocol
- ☐ Route

Q33 At data link layer error detection is achieved by

- ☒ Cyclic Redundancy Code
- ☐ Hamming codes
- ☐ Bit stuffing
- ☐ Equalization

Q34 The physical layer concerns with

- ☒ bit-by-bit delivery
- ☐ process to process delivery
- ☐ application to application delivery
- ☐ none of the mentioned

Q35 In the layer hierarchy as the data packet moves from the upper to the lower layers, headers are

- ☒ Added
- ☐ Removed
- ☐ Rearranged
- ☐ Modified

Q36 Which of the following condition is to be avoided when transferring packets over a medium?

- ☐ Contention
- ☒ Collision
- ☐ Synchronous
- ☐ Asynchronous

Q37 Frames from one LAN can be transmitted to another LAN via the device

- ☐ Router
- ☒ Bridge
- ☐ Repeater
- ☐ Modem

Q38 A list of protocols used by a system, one protocol per layer, is called

- ☐ protocol architecture
- ☒ protocol stack
- ☐ protocol suit
- ☐ none of the mentioned

Q39 In computer network nodes are

- ☐ the computer that originates the data
- ☐ the computer that routes the data
- ☐ the computer that terminates the data
- ☒ all of the mentioned

Q40 A set of rules that governs data communication is referred to as

- ☒ Protocols
- ☐ Standards
- ☐ RFCs
- ☐ None of the mentioned

Q41 Which one of the following is an internet standard protocol for managing devices on IP network?

- ☐ dynamic host configuration protocol
- ☒ simple network management protocol
- ☐ internet message access protocol
- ☐ media gateway protocol

Q42 A connectionless protocol treats each segment

- ☐ Freely
- ☐ Independently
- ☒ Separately
- ☐ Dependantly

Q43 Which one of the following is not an application layer protocol?

- ☐ media gateway protocol
- ☐ dynamic host configuration protocol
- ☒ resource reservation protocol
- ☐ session initiation protocol

Q44 Which one of the following is an internet standard protocol for managing devices on IP network?

- ☐ dynamic host configuration protocol
- ☒ simple network management protocol
- ☐ internet message access protocol
- ☐ media gateway protocol

Q45 When displaying a web page, the application layer uses the

- ☒ HTTP protocol
- ☐ FTP protocol
- ☐ SMTP protocol
- ☐ None of the mentioned

Q46 Electronic mail uses this Application layer protocol

- ☐ HTTP
- ☒ SMTP
- ☐ FTP
- ☐ SIP

Q47 This is not a application layer protocol

- ☐ HTTP
- ☐ SMTP
- ☐ FTP
- ☒ TCP

Q48 An endpoint of an inter-process communication flow across a computer network is called

- ☒ socket
- ☐ pipe
- ☐ port
- ☐ none of the mentioned

Q49 Transmission control protocol is

- ☐ connection oriented protocol
- ☐ uses a three way handshake to establish a connection
- ☐ receives data from application as a single stream
- ☒ all of the options

Q50 Which one of the following is a transport layer protocol used in internet?

- ☐ TCP
- ☐ UDP
- ☒ Both TCP and UDP
- ☐ None of the options

Q51 Transport layer aggregates data from different applications into a single stream before passing it to

- ☒ network layer
- ☐ data link layer
- ☐ application layer
- ☐ physical layer

Q52 Which one of the following extends a private network across public networks?

- ☐ local area network
- ☒ virtual private network
- ☐ enterprise private network

- ☐ storage area network

Q53 Transport layer protocols deals with

- ☐ application to application communication
- ☒ process to process communication
- ☐ node to node communication
- ☐ none of the mentioned

Q54 Network congestion occurs

- ☒ in case of traffic overloading
- ☐ when a system terminates
- ☐ when connection between two nodes terminates
- ☐ none of the mentioned

Q55 Dialogue control and token management are responsibilities of

- ☐ Network layer
- ☒ Session Layer
- ☐ Transport Layer
- ☐ None of above

Q56 Routing is done on which layer

- ☐ Datalink Layer
- ☒ Network Layer
- ☐ Session
- ☐ Presentation

Q57 What is the default subnet mask for a class C network?

- ☐ 127.0.0.1
- ☐ 255.0.0.0
- ☐ 255.255.0.0
- ☒ 255.255.255.0

Q58 Which one of the following is a data link protocol?

- ☐ ethernet
- ☐ point to point protocol
- ☐ hdlc
- ☒ all of the mentioned

Q59 A _____ is a device that forwards packets between networks by processing the routing information included in the packet.

- ☐ bridge
- ☐ firewall
- ☒ router
- ☐ all of the mentioned

Q60 Communication channel is shared by all the machines on the network in

- ☒ broadcast network
- ☐ unicast network
- ☐ multicast network
- ☐ none of the mentioned

Q61 Which one of the following is the multiple access protocol for channel access control?

- ☐ CSMA/CD
- ☐ CSMA/CA

- ☒ CSMA/CD and CSMA/CA
- ☐ None of the mentioned

Q62 CRC stands for

- ☒ cyclic redundancy check
- ☐ code repeat check
- ☐ code redundancy check
- ☐ cyclic repeat check

Q63 Header of a frame generally contains

- ☐ synchronization bytes
- ☐ frame identifier
- ☐ addresses
- ☒ all of the mentioned

Q64 Which one of the following task is not done by data link layer?

- ☐ framing
- ☐ error control
- ☐ flow control
- ☒ channel coding

Q65 The data link layer takes the packets from _____ and encapsulates them into frames for transmission.

- ☒ network layer
- ☐ physical layer
- ☐ transport layer
- ☐ application layer

Q66 A single channel is shared by multiple signals by

- ☐ analog modulation
- ☐ digital modulation
- ☒ multiplexing
- ☐ none of the mentioned

Q67 Wireless transmission can be done via

- ☐ radio waves
- ☐ microwaves
- ☐ infrared
- ☒ all of the mentioned

Q68 The physical layer translates logical communication requests from the _____ into hardware specific operations.

- ☒ data link layer
- ☐ network layer
- ☐ transport layer
- ☐ application layer

Q69 The physical layer is responsible for

- ☐ line coding
- ☐ channel coding
- ☐ modulation
- ☒ all of the mentioned

Q70 The physical layer provides

- ☐ mechanical specifications of electrical connectors and cables
- ☐ electrical specification of transmission line signal level
- ☐ specification for IR over optical fiber
- ☐ all of the mentioned

Q71 Which transmission media has the highest transmission speed in a network?

- ☐ coaxial cable
- ☐ twisted pair cable
- ☐ optical fiber
- ☐ electrical cable

Q72 The _____ is the physical path over which a message travels

- ☐ Path
- ☐ Medium
- ☐ Protocol
- ☐ Route

Q73 At data link layer error detection is achieved by

- ☐ Cyclic Redundancy Code
- ☐ Hamming codes
- ☐ Bit stuffing
- ☐ Equalization

Q74 The physical layer concerns with

- ☐ bit-by-bit delivery
- ☐ process to process delivery
- ☐ application to application delivery
- ☐ none of the mentioned

Q75 In the layer hierarchy as the data packet moves from the upper to the lower layers, headers are

- ☐ Added
- ☐ Removed
- ☐ Rearranged
- ☐ Modified

Q76 Which of the following condition is to be avoided when transferring packets over a medium?

- ☐ Contention
- ☐ Collision
- ☐ Synchronous
- ☐ Asynchronous

Q77 Frames from one LAN can be transmitted to another LAN via the device

- ☐ Router
- ☐ Bridge
- ☐ Repeater
- ☐ Modem

Q78 A list of protocols used by a system, one protocol per layer, is called

- ☐ protocol architecture
- ☐ protocol stack
- ☐ protocol suit
- ☐ none of the mentioned

Q79 In computer network nodes are

- ☐ the computer that originates the data
- ☐ the computer that routes the data
- ☐ the computer that terminates the data
- ☒ all of the mentioned

Q80 A set of rules that governs data communication is referred to as

- ☒ Protocols
- ☐ Standards
- ☐ RFCs
- ☐ None of the mentioned