

CHAPTER SEVEN

Lossless Compression Algorithms

INTRODUCTION

- ☞ An important aspect of communication is transfer of data from the creator to the recipient.
- ☞ **Compression** in computer terms means reducing the physical size of data such that it occupies *less storage space and memory*.
- ☞ It is done by either ***removing the redundancies*** or in some case ***removing the part of the data*** but ***still maintaining the integrity of the data***.

PURPOSES OF DATA COMPRESSION

- ☞ Data storage and transmission cost money.
- ☞ This cost increases with the amount of data available.
- ☞ This cost can be reduced by processing the data so that it takes less memory and less transmission time.

COMPRESSION REQUIREMENTS

- ☞ Compressions in multimedia systems are subjected to certain constraints.
 - ☞ The quality of the reproduced data should be adequate for applications.
 - ☞ The complexity of the technique used should be minimal, to make a cost-effective compression technique.
 - ☞ The processing of the algorithm should not take too long.
 - ☞ Various data rates should be supported.
 - ☞ It should be possible to generate data on one multimedia system and reproduce data on another system.


- 
- ☞ As many applications exchange multimedia data using communication networks, the compatibility of compression is required.
 - ☞ Standards like CCITT, ISO and MPEG are used to achieve this compatibility.

COMMON COMPRESSION METHODS

- ☞ An array of compression techniques has been set by the **CCITT** (International Consultative Committee for Telephone and Telegraph) Group.
- ☞ There are two types of compression:
 - ☞ **Lossless Compression**
 - ☞ **Lossy Compression**

COMMON COMPRESSION METHODS CONT...

- ☞ Data compression is about storing and sending a smaller number of bits.



LOSSLESS COMPRESSION

- ☛ In ***lossless compression***, data are not altered or lost in the process of *compression* or *decompression*.
- ☛ Lossless techniques enable exact reconstruction of the original document from the compressed information.
- ☛ This compression technique is used for *text documents, databases, and text-related objects*.
- ☛ Lossless methods are used when we can't afford to lose any data: legal and medical documents, computer programs.
- ☛ E.g. LZW, Run Length Encoding, Huffman.

LOSSY COMPRESSION

- ☞ There is loss of some information.
- ☞ The loss of this data is such that the object looks more or less like the original.
- ☞ This method is used where absolute data accuracy is not essential.
- ☞ Lossy compression is the most commonly used compression type.
- ☞ This compression technique is used for image documents, audio, and video objects.
- ☞ E.g. JPEG and MPEG

1. LOSSLESS COMPRESSION ALGORITHMS

1.1. Run-length coding (RLC)

- ☞ RLC is a very simple form of data compression in which *runs of data are stored as a single data value* and count, rather than as the original run.
- ☞ This is most useful on data that contains many such runs
- ☞ For instance, simple graphic images such as *icons, line drawings, and animations*.
- ☞ Used for compressing text and black and white image.

RUN-LENGTH CODING (RLC) CONT...

- ☞ Here the consecutive repeated string of characters is replaced by 2 bytes
 - ☞ Where the first byte contains the number which represent the no of times the character is repeated &
 - ☞ The second byte contains the represented character it self.
- ☞ **Disadvantage**: sometimes more no of bits for representing the compressed data as compared to the original data creates negative compression.!

1. LOSSLESS COMPRESSION ALGORITHM CONT..

1.2. Variable-length code

- ☛ In coding theory a variable-length code is a code which *maps source symbols to a variable number of bits*.
- ☛ Certain part of the data appear more frequently than others, so it would be more economic to assign fewer bits as their codes.
- ☛ The more frequent appearing symbols are coded with fewer bits per symbol and vice-versa.
- ☛ Some examples of well-known VLC strategies are Huffman coding, Lempel-Ziv coding and Arithmetic coding.

BASICS OF INFORMATION THEORY

☞ According to the famous scientist Shannon, of Bell Labs, the entropy of an information source with alphabet $S = \{s_1, s_2, \dots, s_n\}$ is defined as:

☞ Entropy is the measure of content in a message

p_i – probability that symbol s_i will occur in S .

$\log_2 \frac{1}{p_i}$ – indicates the amount of information (*self-information* as defined by Shannon) contained in s_i , which corresponds to the number of bits needed to encode s_i .

$$\eta = H(S) = \sum_{i=1}^n p_i \log_2 \frac{1}{p_i}$$

$$= - \sum_{i=1}^n p_i \log_2 p_i$$

- 
- ☞ As can be seen in the above equation the entropy is a weighted-sum of terms ;
 - ☞ hence it represents ***the average amount of information contained per symbol in the source S.***
 - ☞ The entropy specifies the lower bound for the average number of bits to code symbol in S.

Variable-length Coding(VLC)

Shannon-Fano Algorithm

- ☞ The Shannon-Fano algorithm was independently developed by Shannon at Bell Labs and Robert Fano at MIT.
- ☞ To illustrate the algorithm, let us suppose the symbols to be coded are the characters in the word “HELLO”.
- ☞ The frequency count of the symbols is

Symbol	H	E	L	O
Count	1	1	2	15


Shannon-fano Algorithm Cont..

- ☞ A top down approach


- 1. Sort the symbols according to the frequency count of their occurrences.*
- 2. Recursively divide the symbols into two parts, each with approximately the same number of counts, until all parts contain only one symbol.*

- ☞ A natural way of implementing is to build a binary tree.


- ☞ Lets assign 0 to the left branches and 1 to the right branches.



(a)



(b)



(c)


Fig. 7.3: Coding Tree for HELLO by Shannon-Fano.

Result of Performing Shannon-Fano on HELLO


Symbol	Count	$\log_2 \frac{1}{p_i}$	Code	# of bits used
L	2	1.32	0	2
H	1	2.32	10	2
E	1	2.32	110	3
O	1	2.32	111	3
TOTAL number of bits:				10

$$\begin{aligned}\eta &= p_L \cdot \log_2 \frac{1}{p_L} + p_H \cdot \log_2 \frac{1}{p_H} + p_E \cdot \log_2 \frac{1}{p_E} + p_O \cdot \log_2 \frac{1}{p_O} \\ &= 0.4 \times 1.32 + 0.2 \times 2.32 + 0.2 \times 2.32 + 0.2 \times 2.32 = 1.92\end{aligned}$$

- ☛ This suggests the minimum average no of bits to code each character in the word HELLO would be 1.92.
- ☛ Here S-F algorithm uses an average of $10/5=2$ bits to code each symbol which is fairly close to the lower bound of 1.92.
- ☛ Apparently the result is satisfactory.



(a)



(b)

Fig. 7.4 Another coding tree for HELLO by Shannon-Fano.

Symbol	Count	$\log_2 \frac{1}{p_i}$	Code	# of bits used
L	2	1.32	00	4
H	1	2.32	01	2
E	1	2.32	10	2
O	1	2.32	11	2
TOTAL number of bits:				10

Table 7.2: Another Result of Performing Shannon-Fano on HELLO (see Fig. 7.4)

Lempel-Ziv-Welch(LZW) Algorithm

- ☛ It is a dictionary based compression technique.
- ☛ Unlike VLC it uses fixed length code words to represent symbols/characters that commonly occur together.
- ☛ The LZW encoder and decoder build up the same dictionary dynamically while receiving the data.
- ☛ LZW proceeds by placing longer and longer repeated entries into a dictionary, then emitting the code for an element rather than the string it self, if the element has already been placed in the dictionary.

Lempel-Ziv-Welch(LZW) Algorithm cont...

☞ *Algorithm* => **LZW Compression**

BEGIN

 s = next input character;

 while not EOF

 { c = next input character;

 if s + c exists in the dictionary

 s = s + c;

 else

 { output the code for s;

 add string s + c to the dictionary with a new code;

 s = c;

 }

 }

 output the code for s;

END

Lempel-Ziv-Welch(LZW) Algorithm cont...

☞ **Example:** LZW compression for string
“ABABBABCABABBA”

☞ Lets start with a very simple dictionary(string table)
initially containing only 3 characters, with codes as
follows.

☞ Now if the input string is “ABABBABC”
LZW compression algorithm works as f

code	string
1	A
2	B
3	C

Lempel-Ziv-Welch(LZW) Algorithm cont...

s	c	output	code	string
<hr/>				
			1	A
			2	B
			3	C
<hr/>				
A	B	1	4	AB
B	A	2	5	BA
A	B			
AB	B	4	6	ABB
B	A			
BA	B	5	7	BAB
B	C	2	8	BC
C	A	3	9	CA
A	B			
AB	A	4	10	ABA
A	B			
AB	B			
ABB	A	6	11	ABBA
A	EOF	1		

☞ The output codes are:

1 2 4 5 2 3 4 6 1

☞ Therefor instead of sending 14 characters, only 9 codes need to be sent.

☞ If we assume each character or code is transmitted as a byte,
compression ratio = $14/9 = 1.56$

Lempel-Ziv-Welch(LZW) Algorithm cont...

☞ *Algorithm* => **LZW Decompression**

BEGIN

 s = NIL;

 while not EOF

 {

 k = next input code;

 entry = dictionary entry for k;

 output entry;

 if (s != NIL)

 add string s + entry[0] to dictionary with a new code;

 s = entry;

 }

END

Lempel-Ziv-Welch(LZW) Algorithm

cont

Example: LZW

decompression for string
“ABABBABCABABBA”

Input codes to the decoder
are

1 2 4 5 2 3 4 6 1 .

The initial string table is
identical to what is used by
the encoder.

Apparently, the output
string is

“ABABBABCABABBA” a truly

s	k	entry/output	code	string
<hr/>				
			1	A
			2	B
			3	C
<hr/>				
NIL	1	A		
A	2	B	4	AB
B	4	AB	5	BA
AB	5	BA	6	ABB
BA	2	B	7	BAB
B	3	C	8	BC
C	4	AB	9	CA
AB	6	ABB	10	ABA
ABB	1	A	11	ABBA
A	EOF			

Huffman Coding

- ☞ Assign fewer bits to symbols that occur more frequently and more bits to symbols appear less often.
- ☞ There's no unique Huffman code and every Huffman code has the same average code length.

☞ Algorithm:







- ☞ Calculate each frequency of the letters.
- ☞ Order in their frequency the lowest frequency come first.
- ☞ Construct its tree structure (tree for binary code) starting from lowest frequency (lowest frequency is the left side).

Huffman Coding

Frequency of characters

Character	A	B	C	D	E
Frequency	17	12	12	27	32

☛ Example



A: 00	D: 10
B: 010	E: 11
C: 011	

Code

Huffman Coding

☞ Coding

Encoder

Text

EAEBAECDEA

A	→	00	D	→	10
B	→	010	E	→	11
C	→	011			

1100110100011011101100

Huffman code

Huffman code

1100110100011011101100

00	→	A	010	→	B
10	→	D	011	→	C
11	→	E			

Decoder

EAEBAECDEA

Text

☞ Decoding

Class Activity 1

- ☞ Compress and decompress the following data using LZW algorithm.

☐ **DDAACBDDDAABACDDCC**

- ☞ Compress and decompress the following data using Huffman coding method

☐ **MISSISSIPPI**